



Infrared All-in-One Touch Panel Android 11_Series L06

| Model | HS-65IW-L06PA1 | |
|---|---------------------------------------|--|
| Display | Size | 86 inch |
| | Type | a-Si TFT-LCD |
| | Aspect Ratio | 16:9 |
| | Backlight | D-LED |
| | Resolution | 3840×2160 |
| | Refresh Rate | 60Hz |
| | Brightness | 450nits |
| | Contrast Ratio | 5000:1 |
| | Contrast Ratio customize | 500.000:1 |
| | Viewing Angle (CR>10) | 178°/178° (H/V) |
| | Colors | 1.07B(10 bits) |
| | Life(MTBF) | ≥120,000H |
| | Thời gian đáp ứng | 8m/s (G tới G) |
| | Display Area(L*W)/mm | 1428.48(H)*803.52(V) |
| | Glass Material | AG(anti-glare) tempered glass |
| Glass Thickness | 4mm | |
| Glass Hardness | Mohs 7 | |
| Speaker | / | 20W*2 8Ω |
| Power | / | AC:100-240V;60/50Hz; ≤160W; ≤0.5W(Standby) |
| Android | Version | Android 11 |
| | CPU | A73*4 + A53*4 (4 Core+4 Core)2.28GHz |
| | GPU | Mali MP2 |
| | RAM | 8GB LDDR4/3504Mbps |
| | ROM | 64GB EMMC5.1 nand flash |
| | WiFi | IEEE 802.11a/b/g/n/ac (2.4GHz+5GHz) |
| | Analog Signal | VGA Compatible:VGA,SVGA,XGA,WXGA,SXGA, WUXGA |
| Connection | Front | HDMI 2.0 in*1(CEC&ARC) |
| | | USB-C*1 |
| | | USB-A 3.0*3 |
| | | Touch USB *1 |
| | | DP 1.2a in*1 |
| | Rear | HDMI 2.0 in*3(1 HDMI for OPS inside) |
| | | VGA in*1 |
| | | PC Audio in(3.5mm)*1 |
| | | Mic in(3.5mm)*1(support mixing) |
| | | HDMI out*1 |
| | | Spdif out(Optical)*1 |
| | | AV in/out*1 (optional) |
| | | Audio/Earphone (3.5mm)*1 |
| | | Camera USB-C 2.0*1 |
| | | USB-A 3.0*2 |
| USB-A 2.0 Android*1 | | |
| Touch USB *2 | | |
| RJ45 in/out*2(100Mbps in Android, 1000Mbps in OPS, shared ethernet) | | |
| WiFi*1 (Dual ban Wifi) | | |
| Bluetooth*1 | | |
| TF Card*1 | | |
| RS232*1 | | |
| Touch | Touch Performance | Technology: CUSIR - Ultra Slim Infrared Ray; Pen tip > Ø 0.2mm; Touch Precision: ± 2mm; Induction receiving distance: < 1mm; Positioning Precision:<2.8mm; Touch resolution: 32768x32768 |
| | Touch Durability | ≥60,000,000 times.(More than 100,000 hours) |
| | Touch Points | 20-point touch (Windows, Android), 1-point touch (MAC, Linux, Chrome) |
| | Touch Tools | Fingers, pens, or other untransparent objects |
| | Glide speed | Single: ≥2.5ms, Dual: ≥1ms |
| | Response Time | <8ms |
| | Light Resistance | Work normally under 80,000 lux illumination(Full daylight ≈ 100,000 lux) |
| | OS Compatibility | Windows XP/7/8/10; Linux; Chrome OS; Mac OS; Android |
| | Touch Features | Driver-free, calibration-free, waterproof, dustproof, ultra-thin, light |
| Power Supply | <2W, DC 5V±5%, electric current<500mA | |
| Webcam (Optional) | Scan Mode | Progressive |
| | Resolution | 2.07 Megapixel(1080p) |
| | Field of View(FOV) | 90°(horizontal), 60°(vertical) |
| | Type | Open pluggable module, easy to load and unload |
| OPS (Inside) | CPU | Intel® Core i5 11300H Quad Core (8 Thread), 3.1GHz (4.4GHz Turbo), 8MB Cache |
| | RAM | 8GB |
| | Storage | 256GB SSD |
| | Graphics | UHD Graphics for 11th Gen Intel® Processors |
| | Interface (subject to model) | DP 1.2 out / HDMI 1.4 out / RJ45 / USB-A 3.0 / Recover button*1 / Power button*1 |
| Dimension & Weight | Operating System | Windows 10/11 64bit professional(trial) |
| | Physical Dimensions (L*W*T)/mm | 1486*913.2*94 (±5mm) (without wall mount) |
| | Net Weight | 38Kg±1Kg |
| Environmental Requirement | / | Operation temperature:0~40°C; Storage Temperature: -20 ~ 60°C; Operation humidity:20%~80%RH |
| Accessory | / | Interactive pen, remote control, 3m HDMI cable, 3m touch USB cable, 1.8m power cord |

Specifications are subject to change for the better by manufacturer without notice.