# Donview



# Interactive flat panel All in one SERIES L02



Resolution 4K, Antiglare , the hotley, the android and window system window, Mac, Shrome, multi dispay up to 20 screen , Donviewboard software

Donview all invone is a perfect combination of experiences for learning, resolution 4K UHD, Anti-glare tempered glass, built-in stereo speakers, multi-touch, multiple displays at the same time

## **DIFFERENT SIZE**

# 55" 65" 70" 75" 86" 98"



#### Resolution 4K

The high-precision, near-4K resolution interactive display provides stunning visuals that respond to the handwriting experience on every stroke of the screen.

#### Long life

It is among the best in class and ensures a long screen life.

### > Compatibility

Compatible operating system windows, Mac, Chrome

#### Smooth and anti glare surface

Provides super smooth and natural surface, writes fluently, protects against tray scratches, anti-glare

#### User- friendly design

Two hotkeys on either side of the screen Use comfortably and naturally Allows two presenters to use simultaneously

#### Fron connection interface

Multi-input, self-identifying HDMI, USB 3.0, and C style ports













## STRENGTHS OF US SOFTWARE DONVIEW BOARD



Donviewboard software Suitable for interactive software More than 18 languages Diverse library materials to support teaching Interactive simulated experiment in the lesson Note-taking and presentation tools Available for both windows and android operating systems



#### **Speaker appreciation function:**

1. Internet connection, wireless connection with smartphone

2. Display a wireless presentation connection with a smartphone, write or share files to the screen anywhere in the classroom or meeting room.



#### **Donviewshare slideshow function**:

- 1. Download the app for android and apple operating systems
- 2. Windows and Mac OS support
- 3. Easy to connect and interact
- 4. Mirroring projection, data sharing
- 5. Display multiple devices at the same time



DonviewBoard for Windows



DonviewBoard for Android





	SPECIFICATION
Tên	DS-65IWMS-L02PA2
Dimension	65"
Type panel	a-Si TFT-LCD
Aspect ratio	16:9
Backlight	D-LED
Resolution	3840 x 2160
Brightness	450nits
Contrast ratio	5000:1
Angleview	1780
Tempered glass	Anti-glare function, anti-scratch, thickness 4mm, 5mm (customized) bearing Mhos 7
Hot key	18 hot key on right side and left side
Speaker	18W*2
Backlight life	50.000hours
Life time (MTBF)	≥120.000H
Touch point	Multi-touch, 20-point touch and write
Touch skills	Use writing by hand or pen, automatic erasing by palm
Resolution	32768 x 32768
Accuracy	1mm object, response time, speed, single touch < 5ms, multi touch < 7ms
Response time	single touch < 5ms, multi touch < 7ms
Slide mode response time	Single touch: $\geq$ 2.5m/s, Multi touch: $\geq$ 1m/s
Front connector	HDMI*1;TOUCH USB2.0*1; Public Type C*1; Public USB3.0*3
Rear connection port	DP*1; HDMI*1; VGA*1; USB Touch 1:( Type A USB)*1, can be and extender *3; PC audio*1, AV*1, RS232*1, RJ45*1, android USB2.0*1, Public USB3.0*2, Microphone (in/out)_*1
Output connection port	HDMI*1(4K); RJ45*1,
Android	Android 8.0
CPU	Cortex A73*2+A53*2
GPU	Mali G51*4 1.5GHz
RAM	DDR4 4G240MHz
ROM	32GB
Ethernet bandwidth	10/100/1000pbs
Wifi	IEEE 802.11b/g/n/ac 2.4GHz +5GHz, wireless network access connection
Bluetooth	Yes
Firmware function	Multi-monitor integration allows running 2 operating systems in parallel such as android and windows, allowing flexible data sharing via USB
	Software whiteboard (whiteboard), clock, calendar and weather information, internet access (Browser)

Donviewshare	Allows wireless connection of presentations with smartphones and windows, allowing
	wireless connection to smartphones with 2 or more devices at the same time.
Donviewboard software	Whitboard, clock with calendar
Operating system	Window 10 64 Bit (pro) Trial version
Power	Input AC: 100-240V/50Hz-60Hz, output DC 19V/6.8A
Power consumption capacity	165W(Max); ≤0.5W(Standby)
Display size (mm)	1484.3*842.5
Physical dimension (L*W*T)/mm	1532*987.7*102.5/ 1532*987.7*125( với giá treo)
Packing size (L*W*H)/mm	1787*270*1150
Netweight	$45$ kg $\pm 1$ kg
Packing weight	$57$ kg $\pm 1$ kg
Operating temperature and operating	-5°C ~ - 60°C và 10% ~ 90%
humidity	
Storage temperature and storage	-20°C ~ -60°C và 10% ~ 90%
humidity	
Accessories included	2 pens, 1 remote control, 1 power cable, monitor mount



## Shenzhen Donview Electronic Technology Co., Ltd

www.donview.com.cn

y twitter.com/DonviewChina

- f facebook.com/DonviewChina
- in linkedin.com/company/donviewchina